Polisan Moisture Paint (P-MP)

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Specially modified resin-based, aromatic solvent-free, white, ready-to-use, synthetic insulation paint for eliminating moisture and dampness problems caused by weather conditions on the interior and exterior walls of buildings.

PRODUCT FEATURES

High whiteness, does not yellow, ready to use.
Prevents moisture and dampness formation due to excellent moisture and alkali resistance.
Can be applied to all types of damp or dry walls, painted or unpainted surfaces.
Has a mild scent due to the absence of aromatic solvents.
Does not cause blistering on the wall, has high adhesion strength.
Water-based or solvent-based paint can be applied over it upon request

RECOMMENDED FOR

On the interior and exterior walls of buildings
On painted or unpainted damp and moist walls
In basements
On basement walls, tunnels
On surfaces and floors such as plaster, gypsum, concrete, and screed
For moisture and dampness problems

TECHNICIAL SPECIFICATIONS

Touch dry	1	saat
Recoat	8	h
Full dry	24	h

** The provided drying time data are available in 23 ºC ambient temperature and 50 ± 2 % relative humidity conditions.*

SURFACE

It is ready to use and does not require a primer. Dust, blistering, and surface imperfections on the area to be applied should be cleaned and repaired with appropriate filler compounds. The surface to be applied can be damp, moist, or dry. It can be applied to all types of painted or unpainted surfaces.

Polisan Moisture Paint (P-MP)

TECHNICAL DATA SHEET

APPLICATION

The product should be thoroughly mixed for 2-3 minutes after opening the cap of the original packaging.
The surface and ambient temperature should be between +5°C and +30°C. It is applied without thinning using a brush or roller. Two coats should be applied. The second coat should be applied after an 8-hour interval following the first coat. The areas where the product is applied should be well-ventilated, and a mask, gloves, and protective goggles should be worn during application.

Application Conditions

The surface and ambient temperature should be between +5°C and +30°C

Application Tools

Brush

Roll

STORAGE and PACKAGING

Packaging	1 Kg, 2,5 Kg, 5 Kg
Storage Conditions	Direct sunlight the mouth in closed containers must be stored in a cool place. the packaging should be kept sealed when not in use.
Shelf life	24 month
Consumption	500-600 gr/m² (for two coats) depending on the applied surface

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. AŞ
Genel Müdürlük/Fabrika: Demirciler Osb. Mh. Refik Baydur Cd. No:7/3 Dilovası / KOCAELİ Tel: +90 (262) 679 60 00
www.kansaipolisan.com

Rev. no: 01
Publish Date: 28.07.2025