FPB.001-11.01

SAFETY DATA SHEET
BRUT BETON ASTARI

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.
Commission Regulation (EU) 2020/878 of 18 June 2020.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BRUT BETON ASTARI

Product number 608

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Water and copolymer binder based, plaster primer for untreated concrete surfaces, walls and ceilings and paint primer for untreated concrete surfaces. Increases adhesion of cement and gypsum based plasters to surface.

1.3. Details of the supplier of the safety data sheet

Contact person Occupational Health and Safety Department

Manufacturer POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
Demirciler Osb. Mh. Refik Baydur Cd. No:7/3 Dilovası - KOCAELİ
TURKIYE
www.kansaipolisan.com.tr
+90 262 679 60 00
+90 262 606 03 70
info@kansaipolisan.com

1.4. Emergency telephone number

Emergency telephone POLISAN KANSAI BOYA SAN. TİC. A.Ş. : +90 262 679 73 45 ULUSAL ZEHIR DANISMA MERKEZI(UZEM):114

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Classification (Regulation (EC) No. 1272/2008 CLP).

2.2. Label elements

Hazard statements EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Precautionary statements P102 Keep out of reach of children.
P103 Read label before use.
P404 Store in a closed container.
P410 Protect from sunlight.

BRUT BETON ASTARI

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANEDIOL **1-5%**

CAS number: 107-21-1 EC number: 203-473-3

Classification
Acute Tox. 4 - H302
STOT RE 2 - H373

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Get medical attention if symptoms are severe or persist. Never give anything by mouth to an unconscious person. Show this Safety Data Sheet to the medical personnel.

Inhalation N/A

Ingestion IF SWALLOWED: Get medical attention immediately.

Skin contact IF ON SKIN: Wash with plenty of water. Get medical attention if irritation persists after washing.

Eye contact IF IN EYES: Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information Treat symptomatically.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

5.2. Special hazards arising from the substance or mixture

Specific hazards Not relevant. Unusual fire or explosion hazards are not noted.

5.3. Advice for firefighters

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters No specific equipment is mandatory.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes and prolonged skin contact.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

BRUT BETON ASTARI

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Clear up spills immediately and dispose of waste safely. Do not discharge into drains or watercourses or onto the ground.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13. For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container. Protect from freezing and direct sunlight. Keep container dry. Store at temperatures between 5°C and 35°C.

7.3. Specific end use(s)

Usage description Use the product according to its Technical Data Sheet or instructions written on the label.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

No data available.

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour
Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour
Sk
Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate
Sk

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Personal protection Use the personal protective equipments showed above.

Other skin and body protection Avoid contact with skin.

Hygiene measures Wash hands thoroughly after handling.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour The colors covered in the Polisan Color Catalogue.

Odour Characteristic.

pH pH (concentrated solution): 8 - 9

BRUT BETON ASTARI

Flash point	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Relative density	1.65 -1.69 g/cm3
Partition coefficient	No information available.
Viscosity	60000 - 70000 cP @ 25°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under normal conditions.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not relevant.

10.4. Conditions to avoid

Conditions to avoid Avoid freezing.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

ATE oral (mg/kg) 25,050.1

11.2 Information on other hazards

Information on other hazards

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity There are no known harmful effects to the environment.

12.2. Persistence and degradability

BRUT BETON ASTARI

12.3. Bioaccumulative potential

Bioaccumulative potential There is no information about experimantal datas of product

Partition coefficient No information available.

12.4. Mobility in soil

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

Endocrine disrupting properties

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods The generation of waste should be minimised or avoided wherever possible.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN number or ID number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

BRUT BETON ASTARI

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Guidance	Workplace Exposure Limits EH40.

.

15.2. Chemical safety assessment

SECTION 16: Other information

Issued by	FATMA KAZMUTBOLAT / KDU01.21.02
Revision date	30/07/2024
Supersedes date	22/04/2016
SDS number	20380
Hazard statements in full	H302 Harmful if swallowed. H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if inhaled. EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.