

COSMETİKA NACRE

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Acrylic resin based water based,decorative paint giving the surfaces the look of pearl glaze able to create a nacreous appearance.

FEATURES

- Pearlescent
- Odourless
- It has high hiding power.
- Flexible
- Suitable to give nacre effects by special materials according.

RECOMMENDED FOR

Used on interior facades

SURFACE PREPARATION

Surfaces	Surfaces preparatıon
New Surfaces	All surfaces must be dry, smooth and cleaned of dirt and dust.
Previously Painted Surfaces	All surfaces must be dry, smooth and cleaned of dirt and dust.

Cavities and cracks should be filled prior to application. Uniform and flat surfaces can be achieved by Perla Macun (Perla Putty).

APPLICATION

Desired colors of Elegans Matt/Semi Matt or Uniqart Sedef should applied as a first coat 18-24 hours after appliying Transfer Astar. 4 hours later Uniqart Sedef should be applied as a second coat by using a flocculent satin roller. While the top coat is still wet, Nacre effect should be given by the special metal roller recommended by Polisan.

Application Features

Thinning Ratio	No thinning is reguired. It is ready to use.
Application Temperature (ºC)	5-30
Coverage (m^2/L)	15-20 (for single coat)

Application Equipment

Brush	Apply with top quality brush.
Roller	Apply satin roller.

Suggested materials for Decoart Sedef

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 06
Publish Date : 15.10.2024
Sample Text



COSMETİKA NACRE

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

Product Features	Standard

Drying Time (20 °C)

Touch dry (min)	20
Recoat (h)	4
Full dry (h)	4
Dust repellent dry	40

** The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.*

Poz No

Exposure Select No, not if you're looking for options by right-clicking; Add Add to list items already using an optional feature.

STORAGE and PACKAGING

Packaging Information	0.75 L 2.5 L 7.5 L 15 L
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Kansai Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 06
Publish Date : 15.10.2024
Sample Text