FPB.001-11.01

SAFETY DATA SHEET
EPOXY ANTICORROSIVE PRIMER

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended. Commission Regulation (EU) 2020/878 of 18 June 2020.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EPOXY ANTICORROSIVE PRIMER

Product number 609

Container size 1 KG, 3 KG, 20 KG, (A+B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Two-component, reaction drying, epoxy resin based primer cured with polyamide hardener, high filling capacity, forms solid base for paints to be applied on it, good adhesive property.

1.3. Details of the supplier of the safety data sheet

Supplier
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
Demirciler Osb. Mh. Refik Baydur Cd. No:7/3 Dilovası - KOCAELİ
TURKIYE
www.kansaipolisan.com.tr
+90 262 679 60 00
+90 262 606 03 70
info@kansaipolisan.com

Contact person Occupational Health and Safety Department

Manufacturer
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
Demirciler Osb. Mh. Refik Baydur Cd. No:7/3 Dilovası - KOCAELİ
TURKIYE
www.kansaipolisan.com.tr
+90 262 679 60 00
+90 262 606 03 70
info@kansaipolisan.com

.

1.4. Emergency telephone number

Emergency telephone POLISAN KANSAI BOYA SAN. TİC. A.Ş. : +90 262 679 73 45 ULUSAL ZEHIR DANISMA MERKEZI(UZEM):114

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351 Repr. 2 - H361f

Environmental hazards Aquatic Chronic 2 - H411

Classification (Regulation (EC) No. 1272/2008 CLP).

2.2. Label elements

EPOXY ANTICORROSIVE PRIMER

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H361f Suspected of damaging fertility.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing vapour/ spray.
P264 Wash contaminated skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice/ attention.
P310 Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P391 Collect spillage.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/ container in accordance with national regulations.

Contains 4,4'-ISOPROPYLIDENEDIPHENOL, 2-methylpropan-1-ol, 4-methylpentan-2-one

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

4,4'-ISOPROPYLIDENEDIPHENOL **25-40%**

CAS number: 80-05-7 EC number: 201-245-8

Classification
Eye Dam. 1 - H318
Skin Sens. 1 - H317
Repr. 2 - H361f
STOT SE 3 - H335

EPOXY ANTICORROSIVE PRIMER

xylene **10-20%**

CAS number: 1330-20-7 EC number: 215-535-7

Classification
Flam. Liq. 3 - H226
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315

2-methylpropan-1-ol **5-10%**

CAS number: 78-83-1 EC number: 201-148-0

Classification
Flam. Liq. 3 - H226
Skin Irrit. 2 - H315
Eye Dam. 1 - H318
STOT SE 3 - H335, H336

ÇİNKO FOSFAT **5-10%**

CAS number: 7779-90-0 EC number: 231-944-3

M factor (Acute) = 1 M factor (Chronic) = 1

Classification
Aquatic Acute 1 - H400
Aquatic Chronic 1 - H410

4-methylpentan-2-one **1-5%**

CAS number: 108-10-1 EC number: 203-550-1

Classification
Flam. Liq. 2 - H225
Acute Tox. 4 - H332
Eye Irrit. 2 - H319
Carc. 2 - H351
STOT SE 3 - H336

toluene **<1%**

CAS number: 108-88-3 EC number: 203-625-9

Classification
Flam. Liq. 2 - H225
Skin Irrit. 2 - H315
Repr. 2 - H361d
STOT SE 3 - H336
STOT RE 2 - H373
Asp. Tox. 1 - H304

DI-ISOBUTYL KETONE **<1%**

CAS number: 108-83-8 EC number: 203-620-1

Classification
Flam. Liq. 3 - H226
STOT SE 3 - H335

EPOXY ANTICORROSIVE PRIMER

The full text for all hazard statements is displayed in Section 16.

Composition comments The data are given in accordance with the latest EU regulations.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly. Get medical attention if symptoms are severe or persist. Never give anything by mouth to an unconscious person. Show this Safety Data Sheet to the medical personnel.

Inhalation Move affected person to fresh air at once. Get medical attention.

Ingestion DO NOT induce vomiting. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

Skin contact Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention immediately.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Vapours may cause drowsiness and dizziness.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep affected person warm and at rest. Do not induce vomiting.

Eye contact Irritation, burning, lachrymation, blurred vision after liquid splash.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards Not known.

Hazardous combustion products Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting Contain and collect extinguishing water.

Special protective equipment for firefighters Wear chemical protective suit. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid inhalation of vapours and contact with skin and eyes.

For non-emergency personnel No data available.

For emergency responders No data available.

6.2. Environmental precautions

Environmental precautions Avoid or minimise the creation of any environmental contamination. Contain spillage with sand, earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. The product contains a substance which is hazardous to aquatic organisms and which may cause long term adverse effects in the aquatic environment. See Section 12 for additional information on ecological hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Wear eye and face protection. Wear appropriate clothing to prevent any possibility of skin contact.

Advice on general occupational hygiene When using do not eat, drink or smoke. Do not smoke in work area. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes wet or contaminated.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Usage description Use the product according to its Technical Data Sheet or instructions written on the label.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³
Sk, BMGV

2-methylpropan-1-ol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³
Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

4-methylpentan-2-one

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³
Sk, BMGV

toluene

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³
Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³
Sk

DI-ISOBUTYL KETONE

Long-term exposure limit (8-hour TWA): WEL 25 ppm 148 mg/m³
Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through the skin.
BMGV = Biological monitoring guidance value.

8.2. Exposure controls

EPOXY ANTICORROSIVE PRIMER

Protective equipment



Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Use explosion-proof electrical, ventilating and lighting equipment. Static electricity and formation of sparks must be prevented.
Personal protection	Use the personal protective equipments showed above. Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield.
Hand protection	Use protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not eat, drink or smoke when using this product.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
Thermal hazards	No data available.
Environmental exposure controls	Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Flash point	17.5°C Closed cup.
Bulk density	1,50-1,54 kg/m³
Viscosity	90-100 KU @ °C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under normal conditions.

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known.

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented.

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Acids - oxidising.

10.6. Hazardous decomposition products

EPOXY ANTICORROSIVE PRIMER

Hazardous decomposition products	Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - dermal

ATE dermal (mg/kg)	9,357.17

Acute toxicity - inhalation

ATE inhalation (gases ppm)	38,279.34
ATE inhalation (vapours mg/l)	72.44
ATE inhalation (dusts/mists mg/l)	12.76

General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin.
Eye contact	Risk of serious damage to eyes.

11.2 Information on other hazards

Information on other hazards

SECTION 12: Ecological information

Ecotoxicity	The product contains a substance which may have hazardous effects on the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulative potential	There is no information about experimantal datas of product

12.4. Mobility in soil

Mobility	There is no information about experimantal datas of product.

12.5. Results of PBT and vPvB assessment

12.6 Endocrine disrupting properties

Endocrine disrupting properties

12.6. Other adverse effects

Other adverse effects	There is no information about experimantal datas of product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

EPOXY ANTICORROSIVE PRIMER

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. ■ According to the European Waste Catalogue, Waste Codes are not product specific but
application specific. Waste Codes should be assigned by the User based on the application in which the product is used. ● Dispose of by: Burial in a licenced land-fill or incineration in a licenced apparatus (after
admixture with suitable combustible material).

SECTION 14: Transport information

14.1. UN number

UN number or ID number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT (CONTAINS TRIZINC BIS(ORTHOPHOSPHATE))
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ICAO packing group	II
ADN packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-E

EPOXY ANTICORROSIVE PRIMER

ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	According to Regulation EC no: 1272/2008

.

15.2. Chemical safety assessment

SECTION 16: Other information

General information	This safety data sheet information was prepared as a requirement of Chemical Substances Regulations. Product 1 Chapter gives other than those specified. Utilization of the product are beyond our control to special conditions, the supplier, the consumer is responsible for ensuring that the requirements of legislation on the subject. Information consisting of present-day situation in this safety data sheet are based on national legislation, health, safety and environmental respects the way. Technical performance and does not guarantee suitability for specific situations. Based on our present knowledge projects, but they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Key literature references and sources for data	This SDS is prepared based on the information received from the raw material supplier.
Issued by	Emre ÇELİK/ Sertifika Numarası: KDU01.16.11 / Belge Tarihi: 12.04.2021
Revision date	15/12/2023
Revision	01
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H351 Suspected of causing cancer if swallowed. H361d Suspected of damaging the unborn child. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Signature	Emre ÇELİK/Sertifika Numarası: KDU01.16.11/Belge Tarihi: 12.04.2021

EPOXY ANTICORROSIVE PRIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.