EXELANS RESİSTA

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Water based, acrylic coploymer resin based textured matt exterior coating with silicone which can be applied and patterned with afine patterned roller.

FEATURES

-Due to its self-cleaning (Hydron) property.
-Its special formula allows painting all reasons.
-It prevents the accumulated mouisture form damaging interior and exterior surfaces.
-With its highly water repellent property, does not allow surface to permeate water.
-It prevents sunlights making it a long lasting paint.
-Suitable for application in 4 seasons

RECOMMENDED FOR

All kinds of exterior concrete, plaster, bricks and cinder blocks used in the surface.

SURFACE PREPARATION

Surfaces	Surfaces preparatıon
New Surfaces	Dirty or loose textures should be cleaned and primed with A1 Rough Paint Primer
Previously Painted Surfaces	Swelled or dusty parts should be cleaned and primed with A1 Rough Paint Primer .

Lime plastered over with raw surfaces, primer and paint to 1 part vinegar to 1 part water exercise the mixed surface before washing is recommended. The surface cracked should be filled by A1 ACRYLIC PUTTY.

APPLICATION

Applied in one coats.
It can be applied at ambient and surface temperatures between +5 ^{0}C and 35^{0}C. Allow 24 hours after primer application.

Application Features

Thinning Ratio	Ready to use. If necessary, it can be diluted with 5% water by volume.
Application Temperature (ºC)	5 - +35 ºC
Coverage (m^2/kg)	1-1,5 (for a single coat)

Application Equipment

Roller	Apply to roller with coral pattern.

To give the pattern mercan rulo, exterior process roller to spread

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 04
Publish Date : 15.10.2024
Sample Text

EXELANS RESİSTA

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

Product Features	Standard
Drying Time (20 °C)	
Dust free dry (hours)	1-3
Full dry (h)	24

** The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.*

TS Classification

TS 7847 is appropriate and has the TSE.

Poz No
10.300.1064
10.300.1024

STORAGE and PACKAGING

Packaging Information	15 L
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Kansai Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 04
Publish Date : 15.10.2024
Sample Text