FPB.001-11.01

SAFETY DATA SHEET
EXELANS TURBO FLEX C1

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.
Commission Regulation (EU) 2020/878 of 18 June 2020.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EXELANS TURBO FLEX C1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

100% pure acrylic resin-based, flexible, medium-looking texture water-based exterior paint.

1.3. Details of the supplier of the safety data sheet

Contact person Occupational Health and Safety Department

Manufacturer
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
Demirciler Osb. Mh. Refik Baydur Cd. No:7/3 Dilovası - KOCAELİ
TURKIYE
www.kansaipolisan.com.tr
+90 262 679 60 00
+90 262 606 03 70
info@kansaipolisan.com

1.4. Emergency telephone number

Emergency telephone ULUSAL ZEHIR DANISMA MERKEZI(UZEM):114

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Human health For health or environmental hazard under current legislation is not counted. The most recent published account of the product "General Classification guideline for preparations of the EU are required to be labeled due to the calculation procedure.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product isn't flammable.

Classification (Regulation (EC) No. 1272/2008 CLP).

2.2. Label elements

Hazard statements EUH208 Contains . May produce an allergic reaction.

Precautionary statements
P102 Keep out of reach of children.
P103 Read label before use.
P280 Wear protective clothing, gloves, eye and face protection.
P404 Store in a closed container.
P410 Protect from sunlight.

EXELANS TURBO FLEX C1

Supplementary precautionary statements P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANEDIOL **1-5%**

CAS number: 107-21-1 EC number: 203-473-3

Classification
Acute Tox. 4 - H302
STOT RE 2 - H373

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) **<0,003%**

CAS number: 55965-84-9

M factor (Acute) = 100 M factor (Chronic) = 100

SCL:Skin Corr. 1C - H314C ≥ 0,6 %Eye Irrit. 2 - H319: 0,06 % ≤ C < 0,6 %Skin Irrit. 2 - H315: 0,06 % ≤ C < 0,6 %Skin Sens. 1A - H317C ≥ 0,0015 %

Classification
Acute Tox. 3 - H301
Acute Tox. 2 - H310
Acute Tox. 2 - H330
Skin Corr. 1C - H314
Eye Dam. 1 - H318
Skin Sens. 1A - H317
Aquatic Acute 1 - H400
Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information If in doubt, get medical attention promptly.

Inhalation N/A

Ingestion IF SWALLOWED: Get medical attention immediately.

Skin contact IF ON SKIN: Rinse immediately with plenty of water.

Eye contact Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion May cause discomfort if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is non-combustible.

EXELANS TURBO FLEX C1

5.2. Special hazards arising from the substance or mixture

Specific hazards Not relevant.

5.3. Advice for firefighters

Protective actions during firefighting Leave danger zone immediately.

Special protective equipment for firefighters No specific equipment is mandatory.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Risk of contact: Wear protective gloves and goggles/face shield.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Do not discharge into drains or watercourses or onto the ground.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read label before use.

Advice on general occupational hygiene Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a closed container.

7.3. Specific end use(s)

Usage description Use the product according to its Technical Data Sheet or instructions written on the label.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour
Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour
Sk
Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate
Sk

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate ventilation.

Personal protection Use the personal protective equipments showed above.

EXELANS TURBO FLEX C1

Hand protection	Wear protective gloves.
Other skin and body protection	No specific requirements are anticipated under normal conditions of use.
Hygiene measures	Wash skin thoroughly after handling.
Respiratory protection	No specific recommendations.
Environmental exposure controls	Look upto Chapter 6

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	The colors covered in the Polisan Color Catalogue.
Odour	Characteristic.
pH	pH (concentrated solution): 8 - 9
Flash point	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Relative density	1.28-1.32 g/cm3
Viscosity	28000-32000 cps

9.2. Other information

Refractive index	No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under normal conditions.

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not relevant.

10.4. Conditions to avoid

Conditions to avoid	Avoid freezing. No specific requirements are anticipated under normal conditions of use.

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - oral

ATE oral (mg/kg)	25,000.0

EXELANS TURBO FLEX C1

Inhalation No specific health hazards known.

Ingestion May be harmful if swallowed.

Skin contact May cause irritation.

Acute and chronic health hazards May cause discomfort.

Medical considerations No information available.

11.2 Information on other hazards

Information on other hazards

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish LC_{50}, 96 hours: 158 mg/l, Fish

Acute toxicity - aquatic invertebrates EC_{50}, 48 hours: 0,12 mg/l, Daphnia magna

12.2. Persistence and degradability

Persistence and degradability The product is not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential There is no information about experimantal datas of product

12.4. Mobility in soil

Mobility There is no information about experimantal datas of product.

12.5. Results of PBT and vPvB assessment

12.6 Endocrine disrupting properties

Endocrine disrupting properties

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be considered.

Disposal methods No specific equipment is required. Wash the equipments after use.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

UN number or ID number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

EXELANS TURBO FLEX C1

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

According to Regulation EC no: 1272/2008

Guidance Workplace Exposure Limits EH40.

.

15.2. Chemical safety assessment

SECTION 16: Other information

General information	This safety data sheet information was prepared as a requirement of Chemical Substances Regulations. Product 1 Chapter gives other than those specified. Utilization of the product are beyond our control to special conditions, the supplier, the consumer is responsible for ensuring that the requirements of legislation on the subject. Information consisting of present-day situation in this safety data sheet are based on national legislation, health, safety and environmental respects the way. Technical performance and does not guarantee suitability for specific situations. Based on our present knowledge projects, but they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Issued by	NİHAL ŞAHİN /KDU01.27.07
Revision date	26/07/2024
Revision	02
Supersedes date	16/04/2016
SDS number	20814
Hazard statements in full	H301 Toxic if swallowed. H302 Harmful if swallowed. H310 Fatal in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H373 May cause damage to organs through prolonged or repeated exposure if swallowed or if inhaled. EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-4-izothiazolin-3-one. May produce an allergic reaction.

EXELANS TURBO FLEX C1

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.