Marine & Marine AA PU Glue

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

One component, solvent free, polyurethane based adhesive.

FEATURES

- Super resistance to water / moisture
- Resistant to cold.

RECOMMENDED FOR

Used for gluing wood, metal, polyester, stone, glass, ceramic, PVC and other plastic materials. Specially recommended for application in location subject to high level humidity.

SURFACE PREPARATION

Application surfaces should be thoroughly free of dirt, dust, oil and grease. To accelerate the adhesion, surface should be slightly moisturised.

APPLICATION

Apply POLİMARİN ADHESIVE directly from its original packing to the more absorbent of the two surfaces or both of surfaces to be glued, loin and place under a press. Adhesion of surfaces at 23°C and 50±5 % relative humidity will be realised within 2 hours. Due to its foaming character, POLİMARİN ADHESIVE can also be successfully used as a sealant or flexible filling agent.

Application Equipment
Spatula

TECHNICAL SPECIFICATIONS

Polisan Boya San. ve Tic. A.Ş.
Headquarters: İçerenköy Mah. Ali Nihat Tarlan Cad. No:86 Ataşehir 34752 İSTANBUL / **Phone:** +90 (0216) 578 56 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
www.polisan.com.tr

Revision No: 03
Publish Date : 12.03.2023
Sample Text

Marine & Marine AA PU Glue

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Packaging Information	0,75 kg - 0,3 kg
Storage Conditions	Store in a cool and dry place. Consume in 1 year. Do not store in temperatures below 0°C.

PRODUCT DESCRIPTION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

PRODUCT DESCRIPTION

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of Polisan Kansai Paint, and was systematically collected by our field engineers. “Polisan Kansai Paint"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements.
The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, Polisan Kansai Paint will not be held legally responsible.
It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.