Marine & Marine Anti-Aging TEAK OIL WDR

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Specially formulated silicone developed for boats, high-quality, solvent-based product.

PRODUCT FEATURES

- Transparent
- Wood will extend the life by protecting it from water and sunlight.
- It preserves the natural appearance of wood.

RECOMMENDED FOR

Hard interior / exterior wood (teak, etc.), boats, used in garden furniture.

TECHNICAL SPECIFICATIONS

Drying time		
Full dry	2-33	h

The specified drying time; 23 ° C temperature and 50 ± 2% relative humidity is valid.

SURFACE

Surface dirt, dust, grease and residue should be cleaned of old paint and varnish, it must be clean and dry.

Polisan Boya San. ve Tic. A.Ş.
Headquarters: İçerenköy Mah. Ali Nihat Tarlan Cad. No:86 Ataşehir 34752 İSTANBUL / **Phone:** +90 (0216) 578 56 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
info@polisan.com.tr

Revision No : 05
Publish Date: 23.05.2023
Sample Text

Marine & Marine Anti-Aging TEAK OIL WDR

TECHNICAL DATA SHEET

APPLICATION

Application Temperature	:	5 °C - 30 °C
Flash off (room temperature, min)	:	Ready for use. Do not thin.
Covered area (m^2/kg)	:	

Mixing Ratio

:	
:	

For the first application the substrate must be covered in two layers. To ensure the longevity of the wood, every 2-3 months or sooner if the sea water and sun exposure is high, second application is recommended. Teak Oil WDR should be mixed thoroughly before application and should be re-applied from time to time.

Application Equipment

Brush	Available
Sponge	Available

POZ No.

04.506

STORAGE and PACKAGING

Packaging	0,75 L, 2,5 L, 15 L
Storage Conditions	In sealed packaging, store in a cool place.
Shelf life	3 years

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of Polisan Kansai Paint, and was systematically collected by our field engineers. “Polisan Kansai Paint"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements.
The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, Polisan Kansai Paint will not be held legally responsible.
It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Boya San. ve Tic. A.Ş.
Headquarters: İçerenköy Mah. Ali Nihat Tarlan Cad. No:86 Ataşehir 34752 İSTANBUL / **Phone:** +90 (0216) 578 56 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
info@polisan.com.tr

Revision No : 05
Publish Date: 23.05.2023
Sample Text