

Politex Glass Polish Gloss

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Single-component urethane alkyd based air-cured, non-yellowing and scratch resistant, easy-to-apply, high-quality glossy parquet varnish.

PRODUCT FEATURES

- Extremely hard
- Elastic
- High abrasion resistance
- Protects parquets against many abrasive materials like detergent, alcohol, oil, tea, and fruit juice

RECOMMENDED FOR

Can be used to all kinds of parquet surfaces

TECHNICIAL SPECIFICATIONS

Drying time		
Touch dry	6	h
Recoat	12	h
Full dry	12	h

** The provided drying time data are available in 23 ºC ambient temperature and 50 ± 2 % relative humidity conditions.*

Formed chemical and physical durable max. 7 days

SURFACE

For new parquet floors	After scraping and sanding, dust should be removed and saturated with Titanium Anti Aging Universal Impregnated.
For old parquet floors	Old parquet floors polished with wax polish should be screed, cleaned very well of old varnish, and impregnated with Titanium Anti Aging Universal Impregnated. If necessary, fill the gaps between the parquets with a paste prepared with sandpaper and parquet varnish.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters: Hilltown Ofis, Aydınevler Mah. Siteler Yolu Cad. 28 No:1/A Küçükyalı-Maltepe, İstanbul / **Phone:+**90(216) 578 88 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
Mail: info@kansaipolisan.com
www.kansaipolisan.com

Rev. no: 08
Publish Date: 01.03.2024
Sample Text

Politex Glass Polish Gloss



TECHNICAL DATA SHEET

APPLICATION

Stir the container thoroughly before the application. Repeat this step occasionally during application. Apply as two or three coats with aminimum of 12 hours resting time between each coat. Applied in 2 or 3 coats.

Application Temperature	:	min +5 °C / max + 30 °C
Flash off (room temperature, min)	:	Ready to use; but can be thinned with Synthetic Thinner
Coverage (m2/L)	:	14-16 (Single coat)

Application Equipment

Brush	Applicable
Roller	Applicable
Sponge	Applicable

TS CLASSIFICATION

STORAGE and PACKAGING

Packaging	0,75 L, 2,5 L, 12 KG
Storage Conditions	In sealed packaging, store in a cool place.
Shelf life	3 years

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters: Hilltown Ofis, Aydınevler Mah. Siteler Yolu Cad. 28 No:1/A Küçükyalı-Maltepe, İstanbul / **Phone:+**90(216) 578 88 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
Mail: info@kansaipolisan.com
www.kansaipolisan.com

Rev. no: 08
Publish Date: 01.03.2024
Sample Text