FPB.001-11.01

SAFETY DATA SHEET
Special Purpose Spray Gold Foil
Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Special Purpose Spray Gold Foil

Product number 97501...

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fast-drying, solvent-based, decorative and protective spray paint with gold leaf effect. Applied on internal or external surfaces such as wood, metal, glass, ceramic, plastic, paper, cardboard, concrete, artificial flowers. Suitable for use in fields such as machinery, spare parts, steelwork, wood furniture, hard plastic, hobby and handicrafts, motorcycles/bicycles/automobiles.

1.3. Details of the supplier of the safety data sheet

Supplier
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
DİLOVASI O.S.B.
1.KISIM LİMAN CAD. NO:7
DİLOVASI – KOCAELİ
TURKIYE
www.polisan.com.tr
+90 262 754 80 00
+90 262 754 74 34
info@kansaipolisan.com

Manufacturer
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
DİLOVASI O.S.B.
1.KISIM LİMAN CAD. NO:7
DİLOVASI – KOCAELİ
TURKIYE
www.polisan.com.tr
+90 262 754 80 00
+90 262 754 74 34
info@kansaipolisan.com

1.4. Emergency telephone number

Emergency telephone POLISAN KANSAI BOYA SAN. TİC. A.Ş. : +90 262 679 73 45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319


Environmental hazards Not Classified

Human health Prolonged skin contact may cause temporary irritation.

Special Purpose Spray Gold Foil

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.

Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P264 Wash contaminated skin thoroughly after handling.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P102 Keep out of reach of children.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE **25-40%**

CAS number: 67-64-1 EC number: 200-662-2

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

2-METHOXY-1-METHYLETHYL ACETATE **25-40%**

CAS number: 108-65-6 EC number: 203-603-9

Classification
Flam. Liq. 3 - H226

ETHYL ACETATE **5-10%**

CAS number: 141-78-6 EC number: 205-500-4

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Special Purpose Spray Gold Foil

General information	If in doubt, get medical attention promptly. Get medical attention if symptoms are severe or persist. Never give anything by mouth to an unconscious person. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. If breathing stops, provide artificial respiration. For breathing difficulties, oxygen may be necessary. Get medical attention if symptoms are severe or persist.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention. Never give anything by mouth to an unconscious person.
Skin contact	Remove contaminated clothing and shoes, and dispose of them carefully and safely. Wash the exposed area with soap and water. Get medical attention if irritation, swelling or redness develops on the skin and / or if it continues.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information	The product contains a sensitising substance. Treat symptomatically.
Inhalation	May cause irritation of the respiratory tract by inhalation. Long-term inhalation may cause dizziness and drowsiness.
Ingestion	May cause discomfort if swallowed.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat according to instructions.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Foam. Dry chemicals.
Unsuitable extinguishing media	Water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	When heated, vapours/gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not breathe vapour. Wear protective gloves. For personal protection, see Section 8.

Special Purpose Spray Gold Foil

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with sand or other inert absorbent. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For waste disposal, see section 13. For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions The mixture can be electrostatically ignited. It is suitable for use and storage in the environment where Exproof electrical appliances are located. Do not eat, drink or smoke when using the product. Do not use in confined spaces without adequate ventilation and/or respirator. Provide adequate ventilation. Protect against direct sunlight. In accordance with the provisions of the "Regulation on Health and Safety Precautions in Chemical Matters and Procedures" published in the Official Gazette dated 26/12/2003 and numbered 25328 on measures to be taken in works and workplaces working with hazardous chemicals in order to protect health, safety and environment, care should be taken to ensure that the work procedures in the workplace are planned and that organizational measures are taken.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Protect from light. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store in a cool and well-ventilated place. Store away from the following materials: Oxidising materials. Keep out of the reach of children. Keep away from food, drink and animal feeding stuffs.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) Use the product according to its Technical Data Sheet or instructions written on the label. Read label before use.

Usage description Use the product according to its Technical Data Sheet or instructions written on the label.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m3(Sk)
Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m3(Sk)

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm
Short-term exposure limit (15-minute): WEL 400 ppm
WEL = Workplace Exposure Limit

Special Purpose Spray Gold Foil

Ingredient comments	WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	Provide adequate ventilation.
Eye/face protection	Wear chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves. Rubber (natural, latex). Neoprene.
Other skin and body protection	AVOID ALL SKIN AND RESPIRATORY CONTACT! Provide eyewash station. Wear appropriate clothing to prevent any possibility of skin contact. Wear antistatic clothing made from natural yarn or high-temperature resistant synthetic yarn.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Do not smoke in work area.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.
Environmental exposure controls	Look upto Chapter 6

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Yellow.
Odour	Characteristic.
Flash point	41°C CC (Closed cup).
Upper/lower flammability or explosive limits	Not available.
Bulk density	1,5 - 1,6 kg/m³
Viscosity	2500 - 4000 @ °C
Explosive under the influence of a flame	Yes

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable under normal conditions.

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Special Purpose Spray Gold Foil

Possibility of hazardous reactions Not available. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid contact with strong oxidising agents. Avoid exposure to high temperatures or direct sunlight. Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxides. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Hazardous decomposition products Not known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects Carcinogen Category 3.

Skin corrosion/irritation

Skin corrosion/irritation Not known.

Serious eye damage/irritation

Serious eye damage/irritation No information available.

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation No information available.

Acute and chronic health hazards Inhalation May cause respiratory system irritation. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. Prolonged inhalation of high concentrations may damage respiratory system. SKIN CONTACT. Product has a defatting effect on skin. May cause skin irritation/eczema. EYE CONTACT. Irritating to eyes.

Route of entry Inhalation

SECTION 12: Ecological Information

Ecotoxicity Substances in the product are not classified as hazardous to the environment. But, repeated spillages in large amounts may be harmful for the environment and aquatic organisms.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Stability (hydrolysis) No information available.

12.3. Bioaccumulative potential

Bioaccumulative potential Inconclusive data.

12.4. Mobility in soil

Special Purpose Spray Gold Foil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Dispose of in accordance with local and national regulations. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Special Purpose Spray Gold Foil

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972. Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste) Regulations 1980 (as amended).
EU legislation	System of specific information relating to Dangerous Preparations. 2001/58/EC.
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

SECTION 16: Other information

General information	This safety data sheet information was prepared as a requirement of Chemical Substances Regulations. Product 1 Chapter gives other than those specified. Utilization of the product are beyond our control to special conditions, the supplier, the consumer is responsible for ensuring that the requirements of legislation on the subject. Information consisting of present-day situation in this safety data sheet are based on national legislation, health, safety and environmental respects the way. Technical performance and does not guarantee suitability for specific situations. Based on our present knowledge projects, but they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Key literature references and sources for data	This SDS is prepared based on the information received from the raw material supplier.
Revision date	25/12/2017
Revision	02
Supersedes date	12/05/2016

Special Purpose Spray Gold Foil

SDS number 10045

Hazard statements in full

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.