Polisan
HOME COSMETICS



Spray Metallic Colors

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Acrylic based fast-drying, solvent-based, protective and decorative, metallic-effect spray paint.

PRODUCT FEATURES

İt is used for interior and exterior surfaces such as; wood, metal, glass, ceramic, plastic, paper, cardboard, concrete to make flowers and so on. Resistance to UV, difficult weather conditions and water. It has scratching resistance and good impact property. It is free from Lead, atmospheric contaminants and CFC gases that are harmful to the ozone layer and environment.

RECOMMENDED FOR

Machines, spare parts, steel goods, wooden furniture, hard plastic, hobby and handicrafts, motorcycle / bicycle / auto etc. Used in areas.

TECHNICIAL SPECIFICATIONS

Sample Text	**Standard**	
View containing	-	
Smell	-	
Color	Transparant	
Gloss		
Gloss(60°)		
20 °C, Density	0,75-0,80	g / ml
20 °C, Pressure	4,0±0,5	bar
50 °C, Pressure	8,0±0,5	bar
Viscosity Ford Cup 4	11"-12,5"	
Flash Point	Below 0°C	
Teoric Cover Area(m^2/400ml)	2,5-3	
Recomended Number of Layers	2-3	
Thicknes 1. Layer	17	micron
Thicknes 2. Layer	35	micron

** The provided solids, viscosity and density data may vary depending on the color.*

Drying time

Dust-free dry	10-15	min
Touch dry	30-40	min
Recoat	20	min
Full dry	24-30	h

** The provided drying time data are available in 23 ºC ambient temperature and 50 ± 2 % relative humidity conditions.*

SURFACE PREPERATION AND APPLICATION

Before application, thoroughly shake the spray for a minimum of 1 minute. After unlocking the safety catch on the cover, keep the can upright and spray on the application surface from a distance of 25 cm.

Surface Preparation: Before application the surfaceshould be cleaned from dust,dirt ,humidity andgrease and should be used a binder if reuired.

Application: Before application spray should beshaked as well and applied 2-3 times as thin layersfrom the distance 25-30 cm. There should be 20 minutes between the layer applications. After application, if there is paint remaining in can , the canshould be reversed and press pulverizing part inorder to use again later.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters: Hilltown Ofis, Aydınevler Mah. Siteler Yolu Cad. 28 No:1/A Küçükyalı-Maltepe, İstanbul / **Phone:+**90(216) 578 88 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
Mail: info@kansaipolisan.com
www.kansaipolisan.com

Rev. no: 03
Publish Date: 13.07.2020
Sample Text



Spray Metallic Colors

TECHNICAL DATA SHEET

STORAGE and PACKAGING

Packaging	400 ml
Storage Conditions	Should be stored in closed packs without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep packs closed when not in use. Preserve against freezing.
Shelf life	5 years

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters: Hilltown Ofis, Aydınevler Mah. Siteler Yolu Cad. 28 No:1/A Küçükyalı-Maltepe, İstanbul / **Phone:+**90(216) 578 88 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
Mail: info@kansaipolisan.com
www.kansaipolisan.com

Rev. no: 03
Publish Date: 13.07.2020
Sample Text