FPB.001-11.01

SAFETY DATA SHEET
Special Purpose Spray Car Wheel Paints
Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Special Purpose Spray Car Wheel Paints

Product number 97509...

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fast-drying, solvent-based, decorative and protective gloss alloy wheel spray paint. Used to renew and protect automobile rims. Highly resistant to strong weather conditions, abrasion, scratches and fading.

1.3. Details of the supplier of the safety data sheet

Supplier
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
DİLOVASI O.S.B.
1.KISIM LİMAN CAD. NO:7
DİLOVASI – KOCAELİ
TURKIYE
www.polisan.com.tr
+90 262 754 80 00
+90 262 754 74 34
info@kansaipolisan.com

Contact person OHS AND QUALITY & ENVIRONMENT DEPARTMENT

Manufacturer
POLİSAN KANSAI BOYA SAN. VE TİC. A.Ş.
DİLOVASI O.S.B.
1.KISIM LİMAN CAD. NO:7
DİLOVASI – KOCAELİ
TURKIYE
www.polisan.com.tr
+90 262 754 80 00
+90 262 754 74 34
info@kansaipolisan.com

1.4. Emergency telephone number

Emergency telephone POLISAN KANSAI BOYA SAN. TİC. A.Ş. : +90 262 679 73 45

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229 Flam. Liq. 3 - H226

Health hazards Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Special Purpose Spray Car Wheel Paints

Pictogram



Signal word Danger

Hazard statements
H226 Flammable liquid and vapour.
H319 Causes serious eye irritation.
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated

Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 Dispose of contents/ container in accordance with national regulations.
P102 Keep out of reach of children.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ACETONE **25-40%**
CAS number: 67-64-1 EC number: 200-662-2

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

2-METHOXY-1-METHYLETHYL ACETATE **25-40%**
CAS number: 108-65-6 EC number: 203-603-9

Classification
Flam. Liq. 3 - H226

ETHYL ACETATE **5-10%**
CAS number: 141-78-6 EC number: 205-500-4

Classification
Flam. Liq. 2 - H225
Eye Irrit. 2 - H319
STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Special Purpose Spray Car Wheel Paints

Inhalation Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion Not relevant.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation May cause eye and respiratory system irritation.

Ingestion May cause discomfort.

Skin contact The product contains organic solvents.

Eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat according to instructions.

Specific treatments Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products During fire, toxic gases (CO, CO2) are formed.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Face mask, protective gloves and safety helmet. Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not breathe vapour. Eye contact MUST be prevented by means of suitable personal protection equipment. Avoid contact with skin and eyes. Wear protective gloves, eye and face protection.

For non-emergency personnel No data available.

For emergency responders No data available.

6.2. Environmental precautions

Environmental precautions Do not allow water to enter the container as it will react with the product.

Special Purpose Spray Car Wheel Paints

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

Advice on general occupational hygiene Persons susceptible to allergic reactions should not handle this product. Eye wash facilities and emergency shower must be available when handling this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³
Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m3(Sk)
Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m3(Sk)

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm
Short-term exposure limit (15-minute): WEL 400 ppm
WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls Provide adequate general and local exhaust ventilation.

Special Purpose Spray Car Wheel Paints

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	Use protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Odour	Characteristic.
pH	Not applicable.
Flash point	~ -4°C CC (Closed cup).
Partition coefficient	No information available.

9.2. Other information

Other information	No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Flammable/combustible materials.

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid	None known.

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects	Carcinogen Category 3.

Special Purpose Spray Car Wheel Paints

Inhalation May cause respiratory system irritation. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

Skin contact Product has a defatting effect on skin. May cause skin irritation/eczema.

Eye contact Irritating to eyes.

Route of entry Inhalation

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

Toxicity No data available.

12.2. Persistence and degradability

Persistence and degradability No data available.

Stability (hydrolysis) No information required.
Not known.

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

Mobility The product contains volatile substances which may spread in the atmosphere.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects The product contains a substance or substances that will contribute to global warming (greenhouse effect).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Treat dirty and empty storage containers as dangerous to fire and the environment. Must be disposed of in accordance with the "Regulations on Hazardous Waste".

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Special Purpose Spray Car Wheel Paints

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special Purpose Spray Car Wheel Paints

EU legislation

Polisan Kansai Boya Tic. San. A.Ş. assures that our product doesn't contain SVHC substances which are currently in the Candidate List of ECHA.
Please be assured that Polisan Kansai Boya Tic. San. A.Ş. is operating in accordance with REACH legislation and receive updates from Istanbul Mineral and Metals Exporters' Association (IMMEA) REACH Help Desk regarding the changes of the Candidate List and other REACH obligations. We are also aware of our continuing obligations with regard to the dangerous substances restrictions in Annex XVII of REACH. In case of any change of our supply plans and contents of our products in related with REACH, we assure that we will do our best to inform you at the earliest opportunety.

Guidance

Workplace Exposure Limits EH40.
Introduction to Local Exhaust Ventilation HS(G)37.
CHIP for everyone HSG228.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

This safety data sheet information was prepared as a requirement of Chemical Substances Regulations. Special conditions, the supplier of the product are beyond our control utilization, the consumer is responsible for ensuring mandatories of legislation on the subject. This security information is in the form of interest today are based on the national legislation of the state consists of, health, safety and environmental respects the way. For special cases, technical performance and does not guarantee conformance. Given is based on our present knowledge, however, does not constitute a guarantee for any specific product features and shall not establish a legally valid contract.

Issued by Mukaddes AYDIN - 01.61.05

Revision date 14/01/2018

Revision 02

Supersedes date 11/05/2016

SDS number 10334

Hazard statements in full

H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: may burst if heated
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.