

Wood&Wood Anti Aging Teak Oil

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

It is a high quality product with special formula, transparent, silicone additive, wood protection.

FEATURES

- It gives a natural appearance on the applied surfaces,
- Fascination is a deeply penetrating oil,
- Silicone gives water repellent property,
- Thanks to its wood-feeding feature, is a refreshing care product.

RECOMMENDED FOR

It is used for garden furniture made of teak and similar hardwoods to renew natural oils lost by wear and to give shine. The garden park provides easy and quick maintenance of the timber which is exposed to the water such as the sides of the swimming pool and used in the outdoor environment and it extends the life of the timber. At the same time, the wood gives birth and brings vitality and does not disturb the natural appearance.

SURFACE PREPARATION

The surface should be dry and clean, cleaned with mild detergent water, rinsed, dried and then applied by sanding if weathered. The surfaces should be free from all kinds of oil, dirt and loose particles.

APPLICATION

It must be thoroughly mixed before application and this process should be repeated from time to time during application. Garden furniture; In matt furniture; The surface should be dry and clean, apply with sponge at least once, and be sure to remove it with a dry lint-free cloth.

If naked wood is to be applied; For the 1st floor: Wood must be sanded, dusted, brush or sponge should be applied with plenty of sponge. It completes drying in 2-3 hours at 20 ° C.

2nd coat application is recommended for more permanent results. If the second coat is applied, it should wait 1-2 hours. For the second coat, apply with brush or sponge, apply with extra sponge and leave to dry to complete the process. After drying, the surface should be wiped with a dry lint-free cloth.

Application Features	
Thinning Ratio	It is ready to use. No thinning is required
Application Equipment	
Brush	Applicable
Sponge	Applicable

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 06
Publish Date : 22.10.2024
Sample Text



Wood&Wood Anti Aging Teak Oil

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATIONS

Drying Time (20 °C)	
Recoat (h)	8
Full dry (h)	24

** The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.*

STORAGE and PACKAGING

Packaging Information	0.75 L 2.5 L
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

HEALTH AND SAFETY INFORMATION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

LEGAL NOTES

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of PB, and was systematically collected by our field engineers. “Polisan Kansai Boya"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements. The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, PB will not be held legally responsible. It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Kansai Boya San. ve Tic. A.Ş.
Headquarters/Factory: Demirciler osb. mah. Refik Baydur cd. No:7/3 Dilovası/KOCAELİ
Phone: +90 (0262) 679 71 00
www.kansaipolisan.com

Revision No: 06
Publish Date : 22.10.2024
Sample Text