X1 PANEL KAPI BOYASI



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Water based, acrylic resin based, wipeable, odorless, glossy, panel door top coat paint.

FEATURES

- Silk matt
- Preventive and covering

RECOMMENDED FOR

The surface of the primer coated American paneldoor should be cleaned with a damp fabric and then the product can be applied.

SURFACE PREPARATION

American panel doors and moldings.

APPLICATION

It should be applied 2 or 3 times and should wait 2-3 hours between the applications due to the moisture and heat of the room.

Application Features

Thinning Ratio	It is applied without thinning process. If necessary, it can be thinned 5% with water.
Application Temperature (ºC)	5-30
Coverage (m^2 /L)	Approximately 10-15 m^2 /Lt per coat due to the wood's absorbency.

Application Equipment

Brush or roller	
Spray gun	with 150-175 bar; nozzle: should be 0.015-0.021 in.

TECHNICAL SPECIFICATIONS

Drying Time (hour / 20°C) 24

** The specified drying time; temperature, humidity, such media may vary depending on the application thickness and application conditions.*

Poz No

Polisan Boya San. ve Tic. A.Ş.
Headquarters: İçerenköy Mah. Ali Nihat Tarlan Cad. No:86 Ataşehir 34752 İSTANBUL / **Phone:** +90 (0216) 578 56 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
www.polisan.com.tr

Revision No: 07
Publish Date : 11.06.2024
Sample Text

X1 PANEL KAPI BOYASI



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Packaging Information	0.75 L, 2.5 L, 15 L
Storage Conditions	It should be stored in a closed container without being exposed to direct sunlight. The ambient temperature while storage should be between 5-35 °C. Keep container closed when not in use. Preserve against freezing.

PRODUCT DESCRIPTION

Refer to the instructions specified in the harmfulness and precautionary statements on the product packaging.
Product of the safety data sheet should be treated by the rules.
Refer to the nearest health facility for unexpected health problems.

PRODUCT DESCRIPTION

All the information and guidelines given in this technical bulletin was formed and developed through the experience in the laboratories of Polisan Kansai Paint, and was systematically collected by our field engineers. “Polisan Kansai Paint"has the right to make changes in the product where necessary, without notice. The information given above is valid for the product from the date of publication.It is the user's responsibility to verify the accuracy of the information. The product should be used based on the technical information form for the recommended purpose. It is the responsibility of the users to implement all measures for the fulfilment of the specified requirements.
The data in the technical information form is designed to give descriptions of the product performance, under specific test conditions. An important factor in product performance is the variables that may occur in the initial process which should be used as a general guide to the user. Any unauthorised use of this product not covered in the written guidelines, Polisan Kansai Paint will not be held legally responsible.
It is always the responsibility of the user to take all necessary precautions regarding specific requirements of the law set out in local and national legislation. Follow the rules of the safety information provided in the Safety Data Sheet regarding operating procedure of the product, protective equipment, storage, fire and first aid etc. Conditions regarding the use of this product after its end date has no warranty. We can not accept responsibility for products past their expiry date. Responsibility can not be accepted.

Please contact the Technical Service department for more detailed information about the product.

Polisan Boya San. ve Tic. A.Ş.
Headquarters: İçerenköy Mah. Ali Nihat Tarlan Cad. No:86 Ataşehir 34752 İSTANBUL / **Phone:** +90 (0216) 578 56 00
Factory: Dilovası Organize Sanayi Bölgesi 1. Kısım Liman Cad. No:7 Dilovası / KOCAELI **Phone:** +90 (0262) 679 71 00
polisan.com.tr info@polisan.com.tr

Rev. no: 07
Publish date: 11.06.2024

Sample Text